

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

| | | | |
|---------------|-------------------|---------|-----|
| Creation date | 10th June 2022 | | |
| Revision date | 26th January 2023 | Version | 5.0 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture: Lakier PVB 16
UFI: WC00-Y0QU-6002-F0KJ
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Varnish for protecting PCBs
Main intended use
PC-PNT-1 Aerosol paints and coatings
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name: AG TermoPasty Grzegorz Gąsowski
Address: Kolejowa 33 E, Sokoły, 18-218
Poland
Identification number (CRN): 200133730
VAT Reg No: PL9661767714
Phone: 862741342
E-mail: biuro@termopasty.pl
Web address: www.termopasty.pl
Competent person responsible for the safety data sheet
Name: AG TermoPasty Grzegorz Gąsowski
E-mail: biuro@termopasty.pl
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222
Eye Dam. 1, H318
STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes serious eye damage. May cause drowsiness or dizziness.

- 2.2. Label elements**

Hazard pictogram



Signal word

Danger

Hazardous substances

acetone
butan-1-ol

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

| Identification numbers | Substance name | Content in % weight | Classification according to Regulation (EC) No 1272/2008 | Note |
|-------------------------------------------------------------------------------------------------------|----------------|---------------------|--------------------------------------------------------------------------------------------------------------|------|
| Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49-XXXX | acetone | 20-40 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | 1 |
| Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 | butane | 24-32 | Flam. Gas 1, H220 Press. Gas (compressed gas), H280 | 1 |
| Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 | propane | 8-16 | Flam. Gas 1, H220 Press. Gas (compressed gas), H280 | |
| Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 Registration number: 01-2119484630-38-XXXX | butan-1-ol | 5-10 | Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336 | 1 |
| Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX | isopropanol | 5-10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 | 1 |

Notes

1 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

| | | | |
|---------------|-------------------|---------|-----|
| Creation date | 10th June 2022 | | |
| Revision date | 26th January 2023 | Version | 5.0 |

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale gases and vapours. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale gases and vapours. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

| Content | Packaging type | Material of package |
|---------|----------------|---------------------|
| 400 ml | airspray | FE |
| 100 ml | airspray | FE |

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

| Substance name (component) | Type | Value | Note |
|----------------------------|-------------|------------------------|------|
| acetone (CAS: 67-64-1) | OEL 8 hours | 1210 mg/m ³ | |
| | OEL 8 hours | 500 ppm | |

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

| Substance name (component) | Type | Value | Note |
|----------------------------|-----------|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| acetone (CAS: 67-64-1) | WEL 8h | 1210 mg/m ³ | |
| | WEL 8h | 500 ppm | |
| | WEL 15min | 3620 mg/m ³ | |
| | WEL 15min | 1500 ppm | |
| butane (CAS: 106-97-8) | WEL 8h | 1450 mg/m ³ | |
| | WEL 8h | 600 ppm | |
| | WEL 15min | 1810 mg/m ³ | |
| | WEL 15min | 750 ppm | |
| butan-1-ol (CAS: 71-36-3) | WEL 15min | 154 mg/m ³ | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |
| | WEL 15min | 50 ppm | |
| isopropanol (CAS: 67-63-0) | WEL 8h | 999 mg/m ³ | |
| | WEL 8h | 400 ppm | |
| | WEL 15min | 1250 mg/m ³ | |
| | WEL 15min | 500 ppm | |

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

DNEL

acetone

| Workers / consumers | Route of exposure | Value | Effect | Value determination | Source |
|---------------------|-------------------|------------------------|--------------------------|---------------------|--------|
| Workers | Inhalation | 2420 mg/m ³ | Acute effects local | | |
| Workers | Dermal | 186 mg/kg bw/day | Chronic effects systemic | | |
| Workers | Inhalation | 1210 mg/m ³ | Chronic effects systemic | | |
| Consumers | Dermal | 62 mg/kg bw/day | Chronic effects systemic | | |
| Consumers | Inhalation | 200 mg/m ³ | Chronic effects systemic | | |
| Consumers | Oral | 62 mg/kg bw/day | Chronic effects systemic | | |

butan-1-ol

| Workers / consumers | Route of exposure | Value | Effect | Value determination | Source |
|---------------------|-------------------|----------------------|--------------------------|---------------------|--------|
| Workers | Inhalation | 10 mg/m ³ | Chronic effects systemic | | |
| Consumers | Inhalation | 55 mg/m ³ | Chronic effects systemic | | |
| Consumers | Oral | 3.125 mg/kg | Chronic effects systemic | | |

isopropanol

| Workers / consumers | Route of exposure | Value | Effect | Value determination | Source |
|---------------------|-------------------|-----------------------|--------------------------|---------------------|--------|
| Workers | Inhalation | 500 mg/m ³ | Chronic effects systemic | | |
| Workers | Dermal | 888 mg/kg bw/day | Chronic effects systemic | | |
| Consumers | Inhalation | 89 mg/m ³ | Chronic effects systemic | | |
| Consumers | Dermal | 319 mg/kg bw/day | Chronic effects systemic | | |
| Consumers | Oral | 26 mg/kg bw/day | Chronic effects systemic | | |

PNEC

acetone

| Route of exposure | Value | Value determination | Source |
|------------------------------------|-------------------------------------|---------------------|--------|
| Drinking water | 10.6 mg/l | | |
| Marine water | 1.06 mg/l | | |
| Sea sediments | 30.4 mg/kg of food | | |
| Freshwater sediment | 30.4 mg/kg of food | | |
| Soil (agricultural) | 29.5 mg/kg of dry substance of soil | | |
| Microorganisms in sewage treatment | 100 mg/l | | |

butan-1-ol

| Route of exposure | Value | Value determination | Source |
|------------------------------|--------------------------------------|---------------------|--------|
| Drinking water | 0.082 mg/l | | |
| Marine water | 0.0082 mg/l | | |
| Water (intermittent release) | 2.25 mg/l | | |
| Freshwater sediment | 0.178 mg/kg | | |
| Sea sediments | 0.0178 mg/kg | | |
| Soil (agricultural) | 0.015 mg/kg of dry substance of soil | | |

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

isopropanol

| Route of exposure | Value | Value determination | Source |
|------------------------|----------------------------|---------------------|--------|
| Drinking water | 140.9 mg/l | | |
| Marine water | 140.9 mg/l | | |
| Freshwater sediment | 552 mg/kg of dry substance | | |
| Freshwater environment | 552 mg/kg of dry substance | | |
| Soil (agricultural) | 28 mg/kg of dry substance | | |

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------------------------------------------|-------------------------|
| Physical state | gas |
| Colour | colourless |
| Odour | data not available |
| Melting point/freezing point | data not available |
| Boiling point or initial boiling point and boiling range | data not available |
| Flammability | data not available |
| Lower and upper explosion limit | data not available |
| Flash point | data not available |
| Auto-ignition temperature | data not available |
| Decomposition temperature | data not available |
| pH | gas |
| Kinematic viscosity | data not available |
| Viscosity | 44 mPa*s |
| Solubility in water | data not available |
| Partition coefficient n-octanol/water (log value) | data not available |
| Vapour pressure | data not available |
| Density and/or relative density | |
| Density | 0,792 g/cm ³ |
| Relative vapour density | data not available |
| Particle characteristics | data not available |
| Form | liquid |

9.2. Other information

| | |
|----------------------|--------|
| Ignition temperature | 380 °C |
|----------------------|--------|

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

acetone

| Route of exposure | Parameter | Value | Exposure time | Species | Sex |
|--------------------|------------------|-------------------------|---------------|----------------------------------------|-----|
| Oral | LD ₅₀ | 5800 mg/kg | | Rat (Rattus norvegicus) | |
| Inhalation (vapor) | LC ₅₀ | 76000 mg/m ³ | 4 hours | Rat (Rattus norvegicus) | |
| Dermal | LD ₅₀ | 7400 mg/kg | | Rabbit | |
| Dermal | LD ₅₀ | 7400 mg/kg | | Guinea-pig (Cavia aperea f. porcellus) | |

butan-1-ol

| Route of exposure | Parameter | Value | Exposure time | Species | Sex |
|-------------------|------------------|------------|---------------|-------------------------|-----|
| Oral | LD ₅₀ | 2292 mg/kg | | Rat (Rattus norvegicus) | |
| Dermal | LD ₅₀ | 3430 mg/kg | | Rabbit | |
| Inhalation | LC ₅₀ | 17.76 mg/l | 4 hours | Rat (Rattus norvegicus) | |

isopropanol

| Route of exposure | Parameter | Value | Exposure time | Species | Sex |
|-------------------|------------------|-------------|---------------|---------|-----|
| Inhalation | LC ₅₀ | >5 mg/l | 4 hours | Rat | |
| Oral | LD ₅₀ | >2000 mg/kg | | Rat | |
| Skin | LD ₅₀ | >2000 mg/kg | | Rabbit | |

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye damage.

acetone

| Route of exposure | Result | Method | Exposure time | Species |
|-------------------|--------|----------|---------------|---------|
| Eye | | OECD 405 | | |

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

acetone

| Parameter | Value | Exposure time | Species | Environment |
|------------------|------------|---------------|--------------------------------|-------------|
| LC ₅₀ | 8800 mg/l | 48 hours | Invertebrates | Fresh water |
| LC ₅₀ | 2100 mg/l | 24 hours | Invertebrates | Salt water |
| LOEC | 530 mg/l | 8 days | Algae and other aquatic plants | Fresh water |
| NOEC | 430 mg/l | 96 hours | Algae and other aquatic plants | Salt water |
| LC ₅₀ | 5540 mg/l | 96 hours | Fish (Oncorhynchus mykiss) | Fresh water |
| LC ₅₀ | 11000 mg/l | 96 hours | Fish | Salt water |

butan-1-ol

| Parameter | Value | Exposure time | Species | Environment |
|------------------|-----------|---------------|------------------------------------------------------------------|-------------|
| LC ₅₀ | 1376 mg/l | 96 hours | Fish (Pimephales promelas) | |
| EC ₅₀ | 1328 mg/l | 48 hours | Daphnia (Daphnia magna) | |
| EC ₅₀ | 4390 mg/l | 17 hours | Microorganisms (Pseudomonas putida) | |
| EC ₅₀ | 225 mg/l | 96 hours | Algae and other aquatic plants (Pseudokirchneriella subcapitata) | |
| NOEC | 4.1 mg/l | 21 days | Daphnia (Daphnia magna) | |
| EC ₅₀ | 18 mg/l | 21 days | Daphnia (Daphnia magna) | |

isopropanol

| Parameter | Value | Exposure time | Species | Environment |
|------------------|-----------|---------------|-----------------------|-------------|
| LC ₅₀ | >100 mg/l | 48 hours | Fish (Leuciscus idus) | |

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date 10th June 2022
Revision date 26th January 2023 Version 5.0

isopropanol

| Parameter | Value | Exposure time | Species | Environment |
|------------------|-----------|---------------|---------------------------------|-------------|
| EC ₅₀ | >100 mg/l | 48 hours | Daphnia (Daphnia magna) | |
| EC ₅₀ | >100 mg/l | 72 hours | Algae (Scenedesmus subspicatus) | |

Chronic toxicity

acetone

| Parameter | Value | Exposure time | Species | Environment |
|-----------|-----------|---------------|-------------------------------|-------------|
| NOEC | 2212 mg/l | 24 hours | Invertebrates (Daphnia magna) | |

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Data not available.

12.4. Mobility in soil

Data not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

| | | | |
|---------------|-------------------|---------|-----|
| Creation date | 10th June 2022 | | |
| Revision date | 26th January 2023 | Version | 5.0 |


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



Air transport - ICAO/IATA

Packaging instructions passenger 203

Cargo packaging instructions 203

Marine transport - IMDG

EmS (emergency plan) F-D, S-U

MFAG 620

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

| | |
|------|-----------------------------------------------------|
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H280 | Contains gas under pressure; may explode if heated. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |

Guidelines for safe handling used in the safety data sheet

| | |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

| | | | |
|---------------|-------------------|---------|-----|
| Creation date | 10th June 2022 | | |
| Revision date | 26th January 2023 | Version | 5.0 |

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

| | |
|---------------------|---------------------------------------------------------------------------------------------------|
| ADR | European agreement concerning the international carriage of dangerous goods by road |
| BCF | Bioconcentration Factor |
| CAS | Chemical Abstracts Service |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures |
| EC | Identification code for each substance listed in EINECS |
| EC ₅₀ | Concentration of a substance when it is affected 50% of the population |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EmS | Emergency plan |
| EU | European Union |
| EuPCS | European Product Categorisation System |
| IATA | International Air Transport Association |
| IBC | International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods |
| IMO | International Maritime Organization |
| INCI | International Nomenclature of Cosmetic Ingredients |
| ISO | International Organization for Standardization |
| IUPAC | International Union of Pure and Applied Chemistry |
| LC ₅₀ | Lethal concentration of a substance in which it can be expected death of 50% of the population |
| LD ₅₀ | Lethal dose of a substance in which it can be expected death of 50% of the population |
| log K _{ow} | Octanol-water partition coefficient |
| NOEC | No observed effect concentration |
| OEL | Occupational Exposure Limits |
| PBT | Persistent, Bioaccumulative and Toxic |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Agreement on the transport of dangerous goods by rail |
| UN | Four-figure identification number of the substance or article taken from the UN Model Regulations |
| UVCB | Substances of unknown or variable composition, complex reaction products or biological materials |
| VOC | Volatile organic compounds |
| vPvB | Very Persistent and very Bioaccumulative |

| | |
|-------------|--------------------------------------------------|
| Acute Tox. | Acute toxicity |
| Aerosol | Aerosol |
| Eye Dam. | Serious eye damage |
| Flam. Gas | Flammable gas |
| Flam. Liq. | Flammable liquid |
| Press. Gas | Gases under pressure |
| Skin Irrit. | Skin irritation |
| STOT SE | Specific target organ toxicity - single exposure |

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

SAFETY DATA SHEET



according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

| | | | |
|---------------|-------------------|---------|-----|
| Creation date | 10th June 2022 | | |
| Revision date | 26th January 2023 | Version | 5.0 |

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from
the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 5.0 replaces the SDS version from 26 January 2023. Changes were made in sections 1, 2, 13, 15 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.